

AquaSHIELD®

PROTECTIVE ENCLOSURES



**LED Light, Depth 5 1/8 In,
Voltage 120 Red**

LED Warning Light, Steady Burn, Dia 3 1/8 In, Depth 5 1/8 In, Lamp Life 100,000 Hours, 8.2 Candle Power, Voltage 120 VAC, 0.13 Amps AC, 15.6 Watts, Neoprene Rubber Gasket, Lens Design Fresnel, Lens Material Polycarbonate, Glass Filled Polycarbonate Housing Material, Tee Surface Mounting, Type 4X Rating, Operating Temp -31 to 150 F, Color Red, UL, cUL, CSA Standards, Includes Gasket

Warning Lights and Mounting Kit

UL Listed and CSA Certified

LED Steady Burn

(I) Streamline(R) Low Profile LED

Compact design for use in a variety of signaling applications.

Available in 3 mounting configurations. NEMA 4X.

Tech Specs

Item: LED Warning Light

Type: Steady Burn

Color: Red

Height (In.): 3 1/8

Dia. (In.): 5

Depth (In.): 5 1/8

Lamp Life (Hours): 100,000

Candle Power: 8.2

Voltage: 120VAC

Amps AC: 0.13

Watts: 15.6

Gasket: Neoprene Rubber

Lens Design: Fresnel

Lens Material: Polycarbonate

Housing Material: Glass Filled Polycarbonate

Mounting: Surface

Rating: Type 4X

Operating Temp. (F): -31 to 150

Standards: UL, cUL, CSA

Includes: Gasket

Notes & Restrictions Note: FPM: Flashes per minute.